

Inertial Vibration Test System TV 51112-IN

S 51112-IN (Example drawing) (mm)

TECHNICAL PARAMETERS Vibration exciter S 51112-IN

Rated peak force Sine _{pk} /Random _{RMS} ¹	125/70 N
Frequency range	2 - 2000 Hz
Max. displacement Peak-Peak	9 mm
Max. velocity	1.5 m/s
Max. acceleration Sine/Random	0.98/0.54 g
Suspension stiffness	20 N/mm
Effective moving mass	0.35 kg
Total mass	13 kg
Coupling thread	M12



1) Random force according to ISO 5344:2004

SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

Scope of delivery:
Vibration exciter 125 N
Power amplifier 200 VA
Connection cable (3 m)
Power cable (1.5 m)
for amplifier (CEE 7/7 connector)

Options:
Cable extension
Factory acceptance test

Features:
High cross-axial stiffness
Light weight construction by using rare earth magnet
Minimum maintenance effort
Made in Germany
Service hotline

TECHNICAL PARAMETERS Power Amplifier DA 200

Output power _{RMS}	200 VA
Frequency range	1.5 - 22000 Hz
Voltage-/Current mode	yes/no
Voltage _{RMS} , max.	30 V
Current _{RMS} , max.	10 A
Signal input voltage _{RMS}	7 V
Distortion	< 0,1 %
Signal to noise ratio	> 90 dB
Total mass	3.5 kg
Dimensions (WxHxD)	390 x 80 x 260 mm
Power supply (Standard)	1~ / N / PE 100...264 V 50..60 Hz CEE 7/7
Recommended fuse protection (Standard)	10 A slow
Max. power consumption at 230 V	75 VA (operation with S 51112-IN)
Interlocks:	Overload, Temperature, Clipping

Features:

High Signal to noise ratio of >90 dB
Low distortion factor of < 0.1 %
Safety management system monitors functions as temperature, overcurrent and overvoltage

